



## MATERIAL SAFETY DATA SHEET

### PRODUCT

WELDED CARBON STEEL PIPE NIPPLES

FOR TRANSPORTATION EMERGENCIES CONTACT: +62 24 8662598-99

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME : WELDED CARBON STEEL PIPE NIPPLES

APPLICATION/RESTRICTIONS : PIPE

COMPANY IDENTIFICATION : **GROWELL INDO METAL**  
Jl. Tugu Wijaya IV No. 07, Randu Garut,  
Kec. Tugu Kota Semarang, Jawa Tengah 50181

EMERGENCY TELEPHONE NUMBER(S) : +62 24 8662598-99

## 2. HAZARDS IDENTIFICATION

### \*\*EMERGENCY OVERVIEW\*\*

**NOTE:** Steel products under normal conditions do not present an inhalation, ingestion, or contact health hazard. However, operations such as burning, welding, sawing, brazing, grinding and possibly machining, etc. which result in elevating the temperature of the product to or above its melting point or result in the generation of airborne particulates, may present health hazards.

### EFFECTS OF OVEREXPOSURE:

**Major Exposure Hazard: INHALATION**

Chronic inhalation of high concentrations of iron oxide fumes or dusts may lead to a benign pneumoconiosis (siderosis). Inhalation of high concentrations of ferric oxide may possibly enhance the risk of lung cancer development in workers exposed to pulmonary carcinogens.

The inhalation of high concentrations of freshly formed oxide fumes and dusts of Manganese, Copper, Lead and/or Zinc in the respirable particle size range can cause an influenza-like illness termed metal fume fever. Typical symptoms last 12 to 48 hours and are characterized by metallic taste in the mouth, dryness and irritation of the throat, followed by weakness, muscle pain, and chills. No long term effects of metal fume fever have been noted.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

**NOTE:** STEEL PRODUCTS UNDER NORMAL CONDITIONS DO NOT PRESENT AN INHALATION, INGESTION OR CONTACT HEALTH HAZARD (SEE Section 10).

**MATERIAL SAFETY DATA SHEET**

**PRODUCT**

WELDED CARBON STEEL PIPE NIPPLES

FOR TRANSPORTATION EMERGENCIES CONTACT: +62 24 8662598-99

CAS#	Component	Percent
-	Silicon	0.009 - 0.03
7439-96-5	Manganese	0.31 – 0.435
7723-14-0	Phosphorus	0.12 – 0.21
7704-34-9	Sulfur	0.04 – 0.06
7440-62-2	Vanadium	0
7440-50-8	Copper	0.01 – 0.02
-	Nickel	0.01 – 0.02
-	Chromium	0.01 – 0.03
7440-44-0	Carbon	0.06 - 0.09
7439-98-7	Molybdenum	0
7440-21-3	Silicon	0.009 - 0.03
-	Zinc	560 gr/mm2

## MATERIAL SAFETY DATA SHEET

### PRODUCT

WELDED CARBON STEEL PIPE NIPPLES

FOR TRANSPORTATION EMERGENCIES CONTACT: +62 24 8662598-99

(b) Denotes short term exposure limit (STEL).

(c) Denotes "ceiling limit" which is not to be exceeded at any time.

\*Subject to Section EPCRA 313 reporting.

**NOTE:** These products contain trace quantities of various elements but not at reportable levels under the OSHA Hazard Communication Standard Limit (29CFR 1910.1200)

## 4. FIRST AID MEASURES

For overexposure to airborne fumes and particulates, remove exposed person to fresh air. If breathing is difficult or has stopped, administer artificial respiration or oxygen as indicated.

Seek medical attention promptly.

Treat metal fume fever by bed rest, and administer a pain and fever reducing medication.

## 5. FIRE FIGHTING MEASURES

STEEL PRODUCTS IN THE SOLID STATE PRESENT NO FIRE OR EXPLOSION HAZARD

## 6. ACCIDENTAL RELEASE MEASURES

NOT APPLICABLE TO STEEL IN THE SOLID STATE.

## 7. HANDLING AND STORAGE

Operations with the potential for generating high concentrations of airborne particulates should be evaluated and controlled as necessary. Avoid breathing metal fumes and/or dust.

## MATERIAL SAFETY DATA SHEET

### PRODUCT

WELDED CARBON STEEL PIPE NIPPLES

FOR TRANSPORTATION EMERGENCIES CONTACT: +62 24 8662598-99

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**RESPIRATORY:** For welding or burning - NIOSH/MSHA - approved dust and fume respirators should be used to avoid excessive inhalation of particulates. Appropriate respirator selection depends on the magnitude of exposure.

**SKIN:** Protective gloves should be worn as required for welding, burning or handling operations.

**EYE:** Use safety glasses or goggles as required for welding, burning, or handling operations.

**VENTILATION:** Local exhaust ventilation should be provided when sawing, grinding or machining to prevent excessive dust or fume exposure. During welding, burning or brazing please follow the ANSI Standard Z49.1 "Safety in Welding and Cutting"

### OTHER PROTECTIVE EQUIPMENT:

Depending upon the conditions of use and specific work situations, additional protective equipment and/or clothing may be required to control exposures.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### MELTING POINT

**BASE METAL:** @ 2750°

**METALLIC COATING:** @ 800-900°

**APPEARANCE:** Bright metallic

**ODOR:** No Odor

## 10. STABILITY AND REACTIVITY

Stable under normal conditions of use, storage and transport. Will react with strong acid to liberate hydrogen. At temperatures above the melting point of the coating, galvanized pipe may liberate zinc fumes, carbon monoxide and oxides of nitrogen.

## 11. TOXICOLOGICAL INFORMATION

## 12. ECOLOGICAL INFORMATION

**MATERIAL SAFETY DATA SHEET**

**PRODUCT**

WELDED CARBON STEEL PIPE NIPPLES

FOR TRANSPORTATION EMERGENCIES CONTACT: +62 24 8662598-99

**13. DISPOSAL CONSIDERATIONS**

**14. TRANSPORT INFORMATION**

**15. REGULATORY INFORMATION**

**16. OTHER INFORMATION**

**OTHER COMMENTS:**

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:**

Individuals with chronic respiratory disorders (i.e. asthma, chronic bronchitis, emphysema, etc.) may be adversely affected by any fume or airborne particulate matter exposure.

**This information is taken from sources or based upon data believed to be reliable: However PT. GIM makes no warranty as to the absolute correctness or sufficiency of any of the foregoing or that additional or other measures may not be required under particular conditions.**

Prepared By : Handoyo P

Date Issued : March 01, 2021

Replaces : March 01, 2021